

HERCULES

1,9m DYE SUBLIMATION

- First entry level dye-sublimation textile printer of DGI
- Two staggered 4720 printhead for speed and resolution
- Applied 200m roll take-up system
- 2,5L semi-cartridge ink tank system for continuous printing



HERCULES

Print Speed	97m ² /hr	66m ² /hr	51m ² /hr	34m ² /hr
Print Resolution	720 x 600dpi 2Pass	360 x 1,800dpi 3Pass	720 x 1,200dpi 4Pass	720 x 1,800dpi 6Pass
Max Print Width	1,900mm			
Max Media Load	Width : 1,940mm / Diameter : 200mm / Weight : 30kg			
Print Mode	Bi-direction / Uni-direction			
Printhead	Piezo type 4720 Printhead - 2ea			
Color	4 Colors (C, M, Y, K)			
Ink	DGI original water based dye sublimation ink			
Interface	TCP / IP			
Environmental Range	Temperature : 16~28°C Humidity : 35~65% Environmental condition may affect on final printing quality.			
Electricity Requirements	Printer : Single phase 200~240V (50~60Hz), 8A Dryer (front) : Single phase 200~240V (50~60Hz), 18A Dryer (bottom) : Single phase 200~240V (50~60Hz), 10A			

※ All specifications are subject to change without prior notice.

Dimension for Installation

	Uncrated				Crated			
	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
Printer	2,980	840	1,600	370	3,110	990	1,090	660

